

606 TAPE

Double Sided Adhesive Tape

Product Data Sheet

PRODUCT NAME

606 Tape

MANUFACTURER

Polyguard Products, Inc.
Ennis, TX 75119
(214) 515-5000
www.polyguard.com

PRODUCT DESCRIPTION

606 Tape is a high strength, double-sided tape comprised of rubberized asphalt. The tape is supplied in rolls and utilizes both Kraft paper and plastic film release sheets which are removed prior to application.

BASIC USES

606 Tape provides a fast, non-volatile solution for sealing seams and providing tie in details for various Polyguard Membranes including the Underseal® product line.

LIMITATIONS

Material is not UV resistant and exposure should not exceed 7 days. The 606 Tape must be installed to substrates that have been treated with an application of 650 LT Liquid Adhesive, California Sealant or Shur-Tac Liquid Adhesive.

TECHNICAL DATA

See physical properties table.

INSTALLATION

Surface should be clean, dry and free of contaminants before application of the 606 Tape. Because the tape is a double sided tape with paper release on one side and film release on the other, remove the film release sheet. The

606 Tape should be rolled tightly in place to make good contact with the substrate. Press or roll strips to ensure 100% surface adhesion. Application of the 606 Tape should only be applied to substrates that will be covered by membrane or other construction during the same day.

SAFETY

SDS documents for all Polyguard products can be obtained at our website www.polyguard.com. Call Polyguard Products, Inc. at (214) 515-5000 with questions.

WARRANTY

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product are beyond our control; such as weather, workmanship, equipment utilized and prior condition of the substrate. We will replace at no charge product proved to be defective within twelve (12) months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. A five (5) year material or system warranty may be available upon request. Contact Polyguard Products, Inc. for further details.

TECHNICAL SERVICES

Technical assistance, information and Polyguard's products are available through a nationwide network of distributors and architectural representatives, or contact Polyguard Products, Inc.
P.O. Box 755, Ennis, TX 75120-0755
Sales: (615) 217-6061 • Tech Support: (214) 515-5000 • Fax: (615) 691-5500
Email: archtech@polyguard.com
Website: www.polyguard.com

PROPERTY	TEST METHOD	TYPICAL VALUE
COLOR		Black
THICKNESS RESIN LAMINATE (INCL. FIBERS) (MILS) TOTAL COATING THICKNESS GAUGES ARE SUBJECT TO VARIANCES OF ±5%		60 mils
MOISTURE ABSORPTION (%)	ASTM D 570-42	0.2

PACKAGING	PART NUMBER	UNIT SIZE
606 TAPE 4"	60604	4" x 50'
606 TAPE 6"	60606	6" x 50'