

## MATERIALS CHECKLIST

### POLYGUARD<sup>®</sup> AIRLOK<sup>®</sup> FLEX WG LT

#### AIR BARRIER SYSTEM: ABOVE-GRADE FLUID-APPLIED MEMBRANE

#### Polyguard Airlok Flex<sup>®</sup> WG LT

Airlok Flex<sup>®</sup> WG LT is a fluid-applied air barrier coating and is used over CMU, gypsum and wood sheathing. It can be applied in temperatures of 20°F (-7°C) and rising up to a maximum temperature of 65°F (18°C), at an application thickness of 16 to 20 mils wet, and a coverage rate of 80 to 100 SF per gallon (Gypsum board is the standard for coverage, though coverage is inversely related to texture). The VOC content is 115 g/l, and a UV resistance of up to 2 years.

Check	<i>Part Number</i>	<i>Unit Size</i>	<i>Units/pallet</i>	<i>Wt/unit</i>
<b>Polyguard Airlok Flex<sup>®</sup> WG LT</b> <i>Proban<sup>®</sup> mold inhibitor can be added at the factory to Airlok Flex<sup>®</sup> WG LT</i>	ALFLEXWG LT 05	5-gallon pail	36 pails/pallet	55#/pail
	ALFLEXWG LT 50	50-gallon drum	4 dr/pallet	550#/dr
<b>Airlok Flex<sup>®</sup> WG LT System Components (where applicable):</b>	<i>Part Number</i>	<i>Unit Size</i>	<i>Units/pallet</i>	<i>Wt/unit</i>
Detail Sealant PW <sup>™</sup> • 20 oz. sausage	DETAIL SEALANT PW – SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
Detail Sealant PW <sup>™</sup> • 3 gal. pail	DETAIL SEALANT PW – 3 GAL	3-gallon pail	36 pails/pallet	37#/pail
<i>* Detail Sealant PW<sup>™</sup> required in certain details – contact Polyguard Products.</i>				
<b>Possible Accessories:</b>	<i>Part Number</i>	<i>Unit Size</i>	<i>Units/pallet</i>	<i>Wt/unit</i>
Airlok <sup>®</sup> STPE WRB Flash-N-Roll	AIRLOK STPE 2400-2 GAL	2-gallon pail	64 pails/pallet	20#/pail
Airlok <sup>®</sup> STPE WRB Flash-N-Roll	AIRLOK STPE 2400-5 GAL	5-gallon pail	36 pails/pallet	50#/pail
Airlok <sup>®</sup> STPE WRB Gun-N-Spread	AIRLOK STPE 2100-SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
Airlok <sup>®</sup> STPE WRB Detail-N-Joint	AIRLOK STPE 2200-SAU 20 OZ	20 sausages/ctn	45 ctns/pallet	45#/ctn
400 Flashing - 40 mil (6", 9", 12", 18" & TWF)	varies/size	75' roll	36 ctns/pallet	68#/ctn
UV365 <sup>™</sup> Flashing - 40 mil (6", 9", 12", 18" *Window Flashing Only; no TWF)	varies/size	75' roll	36 ctns/pallet	68#/ctn
UV365 <sup>™</sup> Ultra Flashing - 40 mil (6", 9", 12", 18" *Window Flashing Only; no TWF)	varies/size	75' roll	36 ctns/pallet	68#/ctn
<i>Choose product relative to specific application.</i>				
650 LT Liquid Adhesive • 5 gal. pail	650-5 LIQ ADH 5 GA	5-gallon pail	36 pails/pallet	45#/pail
650 LT Liquid Adhesive • 4 – 1 gal. pails	650-5 LIQ ADH 1 GA	4 – 1 gal pails/ctn	54 ctns/pallet	31#/ctn
California Sealant	CALSEAL5	5-gallon pail	36 pails/pallet	45#/pail
Shur-Tac Liquid Adhesive • 5 gal. pail	SHUR-TAC5	5-gallon pail	36 pails/pallet	44#/pail
Shur-Tac Liquid Adhesive • 4 – 1 gal. pails	SHUR-TAC1	4 – 1 gal pails/ctn	54 ctns/pallet	37#/ctn
<i>Polyguard 650 LT Liquid Adhesive, California Sealant, or Shur-Tac Liquid Adhesive are not required as a primer when UV365 Flashing, UV365 Ultra Flashing or 400 Flashing are applied over cured Airlok Flex<sup>®</sup> WG LT.</i>				
Quick Grip Spray Adhesive	QGADH30	30# canister covers approximately 1000 SF		

*Weights listed are estimates.*